


FIG 53



序號 NO.	零件	PART	材 質 MATERIAL
1	閥 體	BODY	ASTM B62-C83600
2	閥 蓋	CAP	ASTM B62-C83600
3	閥 門	DISC	ASTM B62-C83600
4	銷	PIN	ASTM B16-C36000
5	堵 頭	PLUG	ASTM B16-C36000

Features

- T-Type Body
- Swing Disc
- Screwed Cap
- Threaded Ends
- MSS Specification SP-80 Type 3
- CNS-11088 台正字第 4337 號


Working Pressure Non-Shock 最高工作壓力 (靜流水)		Hydrostatic Test Pressure 試驗壓力 (水壓)		
Steam, Water, Oil or Gas 蒸汽 . 水 . 油或氣體	125 psi	Shell Test Pressure 閥體測試壓力	Air 氣壓 80 psi	Water 水壓 300 psi
Cold Working Pressure 常溫工作壓力	200 psi	Seat Test Pressure 閥座測試壓力	80 psi	200 psi

詳細尺寸 Dimension


單位 Unit: 公釐 mm

規格	3/8"	1/2"	3/4"	1"	1-1/4"	1-1/2"	2"	2-1/2"	3"	4"
Size	10	15	20	25	32	40	50	65	80	100
L	54	54	61	70	81	91	109	138	150	180
H	40	39	43	49	55	61	71	83	93	109

FIG 63



O-RING



METAL TO METAL

序號 NO.	零件	PART	材 質 MATERIAL
1	閥 體	BODY	ASTM B62-C83600
2	閥 蓋	CAP	ASTM B62-C83600
3	閥 門	DISC	ASTM B62-C83600
4	O 型環	O-RING	VITON

Features

- Lift Check Design
- Screwed Cap
- Threaded Ends
- MSS Specification SP-80 Type 1

Working Pressure Non-Shock 最高工作壓力 (靜流水)		Hydrostatic Test Pressure 試驗壓力 (水壓)		
Steam, Water, Oil or Gas 蒸汽 . 水 . 油或氣體	125 psi	Shell Test Pressure 閥體測試壓力	Air 氣壓 80 psi	Water 水壓 300 psi
Cold Working Pressure 常溫工作壓力	200 psi	Seat Test Pressure 閥座測試壓力	80 psi	200 psi

詳細尺寸 Dimension

單位 Unit: 公釐 mm

規格	1/4"	3/8"	1/2"	3/4"	1"	1-1/4"	1-1/2"	2"	2-1/2"	3"	4"
Size	8	10	15	20	25	32	40	50	65	80	100
L	45	45	48	56	65	75	84	100	118	136	170
H	29	30	30	34	38	45	51	63	74	87	96