


FIG 54



序號 NO.	零件	PART	材 質 MATERIAL
1	閥 體	BODY	ASTM B62-C83600
2	閥 蓋	CAP	ASTM B62-C83600
3	閥 門	DISC	ASTM B62-C83600
4	銷	PIN	ASTM B16-C36000
5	堵 頭	PLUG	ASTM B16-C36000

Features

- T-Type Body
- Swing Disc
- Screwed Cap
- Threaded Ends
- Full Ports
- MSS Specification SP-80 Type 3


Working Pressure Non-Shock 最高工作壓力 (靜流水)		Hydrostatic Test Pressure 試驗壓力 (水壓)		
Steam, Water, Oil or Gas 蒸汽 . 水 . 油或氣體	150 psi	Shell Test Pressure 閥體測試壓力	Air 氣壓	Water 水壓
			80 psi	450 psi
Cold Working Pressure 常溫工作壓力	300 psi	Seat Test Pressure 閥座測試壓力	80 psi	300 psi

詳細尺寸 Dimension

單位 Unit: 公釐 mm

規格	1/2"	3/4"	1"	1-1/4"	1-1/2"	2"
Size	15	20	25	32	40	50
L	59	69	79	91	101	109
H	37	45	49	60	68	71

FIG 0640



序號 NO.	零件	PART	材 質 MATERIAL
1	閥 體	BODY	ASTM B62-C83600
2	閥 蓋	CAP	ASTM B62-C83600
3	閥 門	DISC	ASTM B62-C83600
4	銷	PIN	ASTM B16-C36000
5	堵 頭	PLUG	ASTM B16-C36000

Working Pressure Non-Shock 最高工作壓力 (靜流水)		Hydrostatic Test Pressure 試驗壓力 (水壓)		
Steam, Water, Oil or Gas 蒸汽 . 水 . 油或氣體	200 psi	Shell Test Pressure 閥體測試壓力	Air 氣壓	Water 水壓
			80 psi	600 psi
Cold Working Pressure 常溫工作壓力	400 psi	Seat Test Pressure 閥座測試壓力	80 psi	400 psi

*Temperature limitation of 450°F (232°C)

Features

- Y-Pattern Body
- Swing Disc
- Screwed Cap
- Threaded Ends
- MSS Specification SP-80 Type 3

詳細尺寸 Dimension

單位 Unit: 公釐 mm

規格	1/4"	3/8"	1/2"	3/4"	1"	1-1/4"	1-1/2"	2"
Size	8	10	15	20	25	32	40	50
L	55	55	64	73	89	112	118	141
H	40	40	45	50	65	78	88	106