


FIG 0642



序號 NO.	零件	PART	材 質 MATERIAL
1	閥 體	BODY	ASTM B61-C92200
2	閥 蓋	CAP	ASTM B61-C92200
3	閥 門	DISC	ASTM B62-C83600
4	銷	PIN	ASTM B16-C36000
5	堵 頭	PLUG	ASTM B16-C36000

Features

- Y-Pattern Body
- Threaded Ends
- Swing Disc
- MSS Specification SP-80 Type 3
- Screwed Cap

Working Pressure Non-Shock 最高工作壓力 (靜流水)		Hydrostatic Test Pressure 試驗壓力 (水壓)		
Steam, Water, Oil or Gas 蒸汽 . 水 . 油或氣體	300 psi	Shell Test Pressure 閥體測試壓力	Air 氣壓	Water 水壓
			80 psi	1500 psi
Cold Working Pressure 常溫工作壓力	1000 psi	Seat Test Pressure 閥座測試壓力	80 psi	1000 psi


*Temperature limitation of 450°F (232°C)

詳細尺寸 Dimension

單位 Unit: 公釐 mm

規格	1/4"	3/8"	1/2"	3/4"	1"	1-1/4"	1-1/2"	2"
Size	8	10	15	20	25	32	40	50
L	55	55	64	73	89	112	118	147
H	40	40	45	50	65	78	88	113

FIG 50



序號 NO.	零件	PART	材 質 MATERIAL
1	閥 體	BODY	ASTM B62-C83600
2	閥 蓋	BONNET	ASTM B62-C83600
3	閥 門	DISC HOLDER	ASTM B16-C36000
4	止洩環	DISC	NBR
5	彈 簧	SPRING	SUS 304
6	墊 片	WASHER	SUS 304
7	螺 帽	NUT	SUS 304

Features

- Spring Loaded Disc Type
- Treaded Ends
- Soft Disc
- MSS Specification SP-80 Type 2
- Integral Bronze Seat

Working Pressure Non-Shock 最高工作壓力 (靜流水)		Hydrostatic Test Pressure 試驗壓力 (水壓)		
Steam, Water, Oil or Gas 蒸汽 . 水 . 油或氣體	150 psi	Shell Test Pressure 閥體測試壓力	Air 氣壓	Water 水壓
			80 psi	450 psi
Cold Working Pressure 常溫工作壓力	300 psi	Seat Test Pressure 閥座測試壓力	80 psi	300 psi

詳細尺寸 Dimension

單位 Unit: 公釐 mm

規格	1/2"	3/4"	1"	1-1/4"	1-1/2"	2"	2-1/2"	3"
Size	15	20	25	32	40	50	65	80
L	53	59	67	78	84	98	119	132
D	15	20	25	32	40	50	65	80