


球狀石墨鑄鐵立式逆止閥

Ductile Iron Lift Check Valve

FIG.69D JIS 10K/KGMC 16K



Features

- Lift Type Disc Design
- Screwed Cap
- Threaded Ends
- Stainless Steel Disc and Seat Ring
- JV 4-2

詳細尺寸 Dimension

規格	3/8"	1/2"	3/4"	1"	1-1/4"	1-1/2"	2"
Size	10	15	20	25	32	40	50
L	65	65	80	90	105	120	140
H	45	45	50	52	64	75	86

單位 Unit: 公釐 mm


序號 NO.	零件	PART	材 質 MATERIAL	
1	閥 體	BODY	FCD 450-10	
2	閥 蓋	CAP	1/2"~3/4"	SUS 410
			1"~2"	FCD 450-10
3	閥 門	DISC	SUS 410	
4	閥體座環	BODY SEAT RING	SUS 410	
5	彈 簧	SPRING	SUS 304	
6	閥蓋襯套	BONNET RING	SUS 410	

Working pressure marking 標 稱 壓 力	16 kgf/cm ²	Hydrostatic test pressure 試驗壓力 (水壓)	
Non-shock water under 120°C 120°C以下之靜流水	14 kgf/cm ²	Shell Test Pressure 閥體測試壓力	20 kgf/cm ²
steam,Air,Oil, Pulse stream under 220°C 220°C以下之 蒸汽、氣體、油、脈動水	10 kgf/cm ²	Seat Test Pressure 閥座測試壓力	15 kgf/cm ²

球狀石墨鑄鐵立式逆止閥

Ductile Iron Lift Check Valve

FIG.69D-G JIS 10K/KGMC 16K



Features

- Lift Type Disc Design
- Screwed Cap
- Viton Disc
- Threaded Ends
- Stainless Steel Disc Holder and Seat Ring
- JV 4-2

詳細尺寸 Dimension

規格	3/8"	1/2"	3/4"	1"	1-1/4"	1-1/2"	2"
Size	10	15	20	25	32	40	50
L	65	65	80	90	105	120	140
H	45	45	50	52	64	75	86

單位 Unit: 公釐 mm

序號 NO.	零件	PART	材 質 MATERIAL	
1	閥 體	BODY	FCD 450-10	
2	閥 蓋	CAP	1/2"~3/4"	SUS 410
			1"~2"	FCD 450-10
3	閥 門	DISC	VITON	
4	閥門支架	DISC HOLDER	SUS 410	
5	閥體座環	BODY SEAT RING	SUS 410	
6	彈 簧	SPRING	SUS 304	
7	閥蓋襯套	BONNET RING	SUS 410	

Working pressure marking 標 稱 壓 力	16 kgf/cm ²	Hydrostatic test pressure 試驗壓力 (水壓)	
Non-shock water under 120°C 120°C以下之靜流水	14 kgf/cm ²	Shell Test Pressure 閥體測試壓力	20 kgf/cm ²
steam,Air,Oil, Pulse stream under 220°C 220°C以下之 蒸汽、氣體、油、脈動水	10 kgf/cm ²	Seat Test Pressure 閥座測試壓力	15 kgf/cm ²